

# Industrial Single Board Computer

## 3.5 inch Miniboard LE-37D

Support Intel® Processor J1900/N2930/E3845 CPU with Onboard VGA, DVI, 2 x LVDS, Display port, HD Audio, Serial ATAI, USB3.0 & 2.0, Gigabit LAN, PCIE Mini card, mSATA



<b>Form Factor</b>	3.5 inch motherboard
<b>CPU</b>	Intel® Processor J1900/N2930/E3845, package type FCBGA1170
<b>Memory</b>	1 x DDR3L (support 1.35V) 1066/1333 SO-DIMM up to 8GB
<b>Real Time Clock</b>	Chipset integrated RTC with onboard lithium battery
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1min/s ~ 255min/s
<b>Power Management</b>	Supports ACPI 5.0 compliant
<b>Serial ATA Interface</b>	1 x serial ATA interface with 300MB/s(3Gb/s) transfer rate
<b>VGA Interface</b>	Intel® Clear Video integrated HD Graphics Technology
<b>DVI Interface</b>	Onboard DVI connector. <i>(DVI and LVDS1 can't be enabled simultaneously)</i>
<b>LVDS Interface</b>	2 x Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply
<b>Display port Interface</b>	Onboard Display port connector. <i>(Display port and LVDS2 can't be enabled simultaneously)</i>
<b>Audio Interface</b>	Realtek ALC262 High Definition Audio Codec
<b>LAN Interface</b>	2 x Intel® I210 Gigabit LAN
<b>GPIO interface</b>	Onboard programmable 8-bit Digital I/O interface.
<b>Extended Interface</b>	2 x PCIE Mini card(1 x mSATA option), 1 x SIM socket, 1x CFast <i>(CFast and mSATA can't be enabled simultaneously)</i>
<b>Internal I/O Port</b>	4 x RS232, 1 x RS232/422/485, 1 x GPIO, 1 x Audio connector, 1 x SMBUS connector, 1 x CRT, 2 x LVDS, 1 x LPC, 4 x USB 2.0(XHCI) and 1 x SATAII
<b>External I/O Port</b>	1 x RS232, 1 x DVI port, 1 x Display port, 2 x RJ45 LAN ports, 1 x USB 3.0(XHCI)/2.0(EHCI) port, 1 x USB 2.0 ports(EHCI).
<b>Power Requirement</b>	6~27V full range DC Input
<b>Dimension</b>	146mm x 101mm
<b>Temperature</b>	Operating within 0~60 °C (for LE-37DJ and LE-37DN serial) Operating within -40~75 °C (for LE-37DE serial)

### Ordering Code

<b>LE-37DJIP</b>	Intel Celeron Processor J1900 (2M Cache, 2.42GHz), DVI, Display Port, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA ,CFast
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Taiwan Commate Computer Inc.

19F., No.94, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22102, Taiwan.

TEL: +886-2-26963909

Website:[www.commell.com.tw](http://www.commell.com.tw)

FAX: +886-2-26963911

E-mail:[info@commell.com.tw](mailto:info@commell.com.tw)



Stage For Your Success

# Industrial Single Board Computer

<b>LE-37DNIP</b>	Intel Celeron Processor N2930 (2M Cache, 2.16GHz), DVI, Display Port, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA, CFast
<b>LE-37DEIP</b>	Intel Atom Processor E3845 (2M Cache, 1.91GHz), DVI, Display Port, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA, CFast
<b>LE-37DJX2</b>	Intel Celeron Processor J1900 (2M Cache, 2.42GHz), 2 x LVDS, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA, CFast
<b>LE-37DNX2</b>	Intel Celeron Processor N2930 (2M Cache, 2.16GHz), 2 x LVDS, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA, CFast
<b>LE-37DEX2</b>	Intel Atom Processor E3845 (2M Cache, 1.91GHz), 2 x LVDS, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card, SMBUS, GPIO, SIM, LPC, mSATA, CFast

## Taiwan Commate Computer Inc.

8F, 19F NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:[www.commell.com.tw](http://www.commell.com.tw)

FAX: +886-2-26963911

E-mail:[info@commell.com.tw](mailto:info@commell.com.tw)



Stage For Your Success