

E Series

Infrared touchscreen



E-Series touchscreen is the lowest profile Infrared touch screen product with integrated touch controller on the bezel. It is designed to fit into LCD monitor. Features such as superior image quality, together with scratch proof, water proof, maintenance free, as well as sunlight operability make the E-series IRTOUCH touchscreen an ideal choice for many interactive applications such as POS, touch monitors and Kiosks.

E Series Touchscreen product List (The types and specifications are only for your reference, please contact us for details)

Size (Inch)	Model	Touchscre Thickness (mm)	Touch Active Area			OutsideDimensions		Drawing
			Height (mm)	Width (mm)	Diagonal (mm)	Height (mm)	Width (mm)	
6	E06	8.3	99.4	132.5	163.64	136	169	E06View
8	E08	6.8	128.6	171.6	214.44	161.6	210.6	E08View
10	E10	6.8	158.4	211.2	264	191.4	244.2	E10View
12	E12	6.8	185.2	246.4	308.24	220.7	281.9	E12View
15	E15	6.8	230	306	382.8	266	342	E15View
17	E17	6.8	272	340	435.41	308	376	E17View
19	E19	6.8	303	378	484.45	339	414	E19View
19	E19(W)	8	257	411	484.74	297	451	E19(W)
21	E21(W)	8	269	477.5	548.1	309	517.5	E21(W)
24	E24(W)	8	324	518.4	611.3	364	558.4	E24(W)

Benifits:

- Vandal proof, wear-resistant
- Maintenance free, longer life expectancy
- Fault tolerance design to ensure reliability
- Versatile touch object
- Super transparency
- Integrated controller
- Operable in various light conditions, indoor and outdoor

Typical Applications:

- POS
- Desktop touch monitor
- Indoor/outdoor kiosk
- ATM
- In-vehicles and transportation
- Medical instrument
- Industrial control systems
- Gaming machine
- Ticket machine

Size

General Size	6.4" to 24"
Customized Size	5.7" to 24"
Fit in with	Panel display device

Performance

Resolution (Interpolation)	4096*4096
Linearity Error	1.5mm

Mechanical

Input Method	Finger, gloved hand or opaque object
Touch Times	Unlimited
Touch Activation Force	No minimum touch activation force is required with IR touch technology
Minimum Touch Object	8mm
Vandal-proof	Can meet ball drop test (1.040kg, 63.5mm diameter ball dropped from height of 1.0m)
Surface Durability	Surface durability is that of glass, Mohs' hardness rating of 7

Optical

Light Transmission	≥92%, up to 100% (no glass)
--------------------	-----------------------------

Environmental

Temperature	Operating: -20°C~70°C Storage: -40°C~85°C
Relative Humidity	Operating: 90% RH (non condensing at max 40°C) Storage: 90%RH (non condensing at max 40°C)
Altitude	Up to 3,000m
Seal ability (front panel)	IP 65
Life Time	At least 7-year

Electrical

Operation Voltage	Typical +DC 5V, +4.75V to +5.25V
Power Supply	USB or PS/2 Interface, power ripple max. 200mV rms
Power	<1W, operating current <200mA
Agency Approvals	CE, FCC Class B
Interface	USB/EIA-232E
Operation System	Windows7\Vista\XP\2003\2000\CE, Linux, MacOS

Ile-de-France

ZAC des Radars
7 rue Jean-Jacques Rousseau
91350 GRIGNY
Tel : (33) 01.69.06.17.90
Fax : (33) 01.69.43.37.32

Sud-Ouest

ZI du Casque
2 rue Jean-Baptiste Senderens
31270 CUGNAUX
Tel : (33) 05.61.06.82.10
Fax : (33) 05.61.06.79.88

Montpellier

Parc d'activités « La Tuilerie »
7 rue Gaston Planté
34790 GRABELS
Tel : (33) 04.99.233.233
Fax : (33) 04.99.233.239