


Features

- Fanless Design
- IP 65 compliant except I/O side
- Intel® Atom™ 1.6GHz Processor, FSB 533MHz
- One 200-pin SO-DIMM socket, up to 2GB DDR2 533MHz SDRAM
- 11~32V DC wide-ranging power input
- Sealed 5-Wire Resistive Touch Screen, Optional for GFG Resistive Touch Screen



Specifications

System	
Processor	Intel® Atom™ Processor N270 1.6GHz built-in, FSB533MHz
System Memory	1 x 200-pin SO-DIMM socket, support 533MHz up to 2GB SDRAM
System Chipset	Intel® 945GSE + ICH7M
External I/O Port	- 4 x USB ports - 2 x RJ-45 ports - 1 x DB-9 , COM2 - 1 x Audio MIC, Line-in, Line-out by cable - 1 x 3-pin DC Power input terminal - 1 x DB-15 VGA - 1 x Power Switch (ATX) - 1 x DB-9 RS-232 (COM 1) (RS-232/422/485 selection, default RS-232)


LCD	
Display Type	19" TFT-LCD
Max. Resolution	1280x1024
Max. Color	16.2M
Luminance (cd/m²)	300
View Angle	H:140° / V:125°
Backlight Lifetime	50,000 hrs

Touch Screen	
Type	Analog resistive (optional)
Light Transmission	80%

Power Supply	
Power Input	DC 11~32V

Mechanical	
Construction	Stainless steel front bezel and Aluminum extrusion back cover
IP Rating	IP 65 except I/O side
Mounting	Panel / VESA 75 x 75 Mount
Dimension	470(W)x388.6(H)x70.8(D)mm
Net Weight	13.2 kgs

Dimension



Environmental	
Operating Temperature	0~50 °C
Storage Temperature	-20~60 °C
Storage Humidity	10~90% @40 °C non-condensing
Certificate	Meet CE/FCC Class A

Ordering Information	
APC-3984T	19" Intel N270 1.6GHZ Ultra Slim IP65 Stainless Steel Fanless Panel PC w/Touch Screen