

Industrial Panel PC

12" Ultra Slim Celeron M Stainless Steel Fanless Panel PC

APC-3280



Features

- Ultra slim, sealed stainless steel enclosure
- Supports Intel Celeron M 1GHz up to Pentium M 1.6GHz CPU
- IP 65 Compliant except I/O side
- Fanless and low-power consumption
- Enhanced safety glass or optional resistive touch screen
- Support wireless and Blue tooth (optional)
- Support VESA 75 mount
- DC 11~28V wide-range power input

System Specifications

CPU	Intel Celeron M 1GHz up to Pentium M 1.6GHz
DRAM	1 x DDR SO-DIMM socket, support DDR 200/266 up to 1GB
Storage	Space for 1 x 2.5" HDD or 1 x CF slot
I/O Ports	1 x DC power input, 1 x COM , 1 x PS/2 keyboard & mouse , 4 x USB 2.0, 1 x Audio Mic, Line-in, Line-out, 1 x VGA, 1 x LAN
Expansion	No Expansion slot
Fanless / Fan	Fanless
Touch screen	Analog resistive (optional)

Display Specifications

LCD	12.1" SVGA
Resolution	800x600
Luminance	400 cd/m ²
Backlight Lifetime	50,000hrs
Dimension	330(W) x 260(H) x 59(D)mm

Mechanical Specifications

Construction	Stainless steel enclosure for IP 65 on 5 sides (except I/O ports)
Power input	DC 11~28V
Operating Temperature	0~50° C
Storage Temperature	0~60 °C
Relative Humidity	5~95% @40 ºC, Non-condensing
Vibration	5~17Hz, 0.1" double amplitude peak to peak
Shock	10G acceleration peak to peak (11ms)
Certificate	Meet CE / FCC Class A
Rating	NEMA 4/IP 65 compliant front bezel
Mounting	VESA 75 mount

Dimensions

