



Features

- Fanless Industry Embedded platform
- Intel® Atom N270 1.6 GHz Processor, 533 MHz FSB
- Intel® 945GSE North & ICH 7-M South Bridge Chipset
- On board DDR 2 memory + SODIMM, Up to 1.5 GB w/o ECC
- 1 Mini PCI, 1 Mini PCI-E & 2 PCI-32 expansion slot
- Extra support RS-422/485 w/ isolation
- Total 22 D-IN & 20 D-out w/ isolation
- DC: 9V ~ 30V power input

Cable-Free

Specifications

Fanless platform

- Low power low operation temperature
- Fanless Aluminum Alloy Embedded System

Dimension

- 235.6 (W) x 125 (H) x 230 (D) mm, Compact size

Processor

- Support Intel® Atom N270 1.6 GHz low power Processor
- 437 pins package, 533 MHz FSB, 512KB L2 Cache

Chipset

- Intel® 945GSE North & ICH 7-M South Bridge Chipset

Memory

- On board 512MB + 1 SODIMM Socket,
Up to 1.5 GB w/o ECC, 533 MHz DDR 2 Memory

BIOS

- Award System BIOS
- Support Console Redirection & Power On After Power failure

Disk Drive Storage

- 1 channel SATA interface + 1 internal CF module slot

Expansion

- 1 Mini PCI + 1 Mini-PCI-E + 2 PCI-32 expansion slot

Ethernet

- 1 Realtek 8111C 100/1000 Mbps LAN interface with Wake-On-LAN & DMI
- Support S/W power ON/OFF function

Watchdog timer

- Programmable WDT from 1 to 255 seconds/minutes

Display Function

- Support high resolution 1080i VGA display

Hardware Monitor

- Monitors Voltage, Temperature

Support RTC & CMOS RAM

- Support Real Time Clock feature
- 256 bytes CMOS RAM built-in chipset

Audio

- ALC662-GR Codec supports Speaker-out

RS-232 / 485 supports

- 1 DB-9 RS-232/485 w/ optional DC-output, 1 DB-9 RS-232

Extra support RS-422/485 w/ isolation protection

- Signal w/ 2500 Vrms isolation protection (1 sec)
- 5V Power w/ 3000V DC isolation protection
- External jumper wire Enable/Disable Termination Resistor

Support Digital I/O w/ isolation protection

- 22 D-In, supports Dry / Wet contact, low level 0~3V, High level 10 ~ 50V. 2500V isolation protection
- 20 D-Out, 500 mA drive capability. 2500V isolation protection

Super I/O

- ITE 8712 & Fintek 81216 Super I/O for KB, MS, COM, Thermal monitor, Voltage monitor

Front panel Extend I/O

- 2 LED, Power switch & Reset
- 4 DIN connector for 19 channels D-IN & 18 channels D-OUT

Rear panel Extend I/O

- Screw-Lock DC-9 ~ 30V power input, 3-pin connector
- 1 DB-9 for RS-232, the other DB-9 for RS-232/485, 2 DIN connector for 2 RS-422/485
- 1 DIN connector for 3 D-in + 2 D-out, 1 DB-15 for VGA
- USB x 4, 1 RJ-45 100/1000 Mbit LAN connector
- 1 Speaker out connector
- Power LED + HDD LED, 1 Power button

Internal I/O interface

- 1 Mini PCI + 1 Mini-PCI-E expansion slot
- 1 CF slot, 1 SATA storage interface
- Total up to 4 D-In, 4 D-Out internal connector
- 1 x 5.1 channel Audio, CD-in, pin header
- 1 x 18-bit dual channel LVDS connector

Power Supply

- DC: 9V~30V / 1.5~5 A input

Power ON/OFF mode

- AT or ATX Power ON/OFF mode

Environment

- Operation temperature: -20°C ~ 50°C
- Storage temperature: -40°C ~ 80°C
- Relative humidity: 10% ~ 90% (Non-condensing)

Certification

- CE / FCC Class A

Ordering Guide

Specification may change without notice

Ordering NO.	CPU	Memory	DB-9 RS-232/485	Isolation RS-422/485	Isolation D-I/O	GPS / HSDPA	PCI-32 slot
Pipal 2032D-835	N270 1.6Ghz	512MB	232/485x1, 232x1	2	22 D-IN, 20 D-OUT	N/A	2


Optional order :

- 60W / 120W Power Adapter, HDD, SODIMM Memory
- Wireless LAN Module, Anti-Vibration HDD drive bay

www.arinfotek.com



Pipal 2032D rear I/O



Dimension: without mounting kit 208 W x 115 H x 230 D mm
with mounting kit 235.6 W x 125 H x 230 D mm

Pipal 2032D front I/O

