

Open Frame LCD

Open Frame LCD



21.5" (16:9)

Specifications


RoHS
COMPLIANT
2002/95/EC

Model Name	W22L100-OFA3
Viewable Size Image	21.5"(16:9)
Active Display Area(mm)	476.64 (H) x 268.11 (V)
Pixel Pitch(mm)	0.248 (H) x 0.248 (V)
Number of Pixels	1920x1080
Contrast Ratio	1000:1(typ.)
Display Color	16.7M(8bit/color)
Brightness(cd/m ²)	250(typ.)
Viewing Angle(CR>=10)	170 (H); 160 (V)
Synchronization Range	
Horizontal/Vertical	31.5~80.0KHz / 60~75Hz
Recommended Resolution	1920x1200 @ 60Hz
Signal Connector	15 pin D-sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	50W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive

Remarks: W22L100 series= VGA input only

W22L110 series= VGA+Video Input

Mechanical Drawing



* Note: this is a simplified drawing and some components are not marked in detail.
Please contact our sales representative if you need further product information.

Rev.	Reasons	Revised Date
1.0	First release	Dec-15-09