

Chassis Monitor

12.1"

Specifications

RoHS
COMPLIANT
2002/95/EC


Model Name	R12T600-CHL1
Viewable Size Image	12.1"
Active Display Area(mm)	246.0(H)x184.5(V)
Pixel Pitch(mm)	0.3075(H)x0.3075(V)
Number of Pixels	800x600
Contrast Ratio	500:1(typ.)
Display Color	262144(6bit/colors)
Brightness(cd/m ²)	400(typ.)
Viewing Angle(CR>=10)	-70~70(H); -50~60(V)(typ.)
Synchronization Range	31.5~46.9KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	800x600@60Hz, 75Hz
Signal Connector	15 pin D-sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	15W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	No
Optional Touch Screen	Resistive, Capacitive

Remarks: R12T600 series= VGA input only

R12T630 series= VGA+Video Input



Mechanical Drawing



* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.