

## Chassis Touch Monitor



**26"(16:9)**

### Specifications

**RoHS**  
COMPLIANT  
2002/95/EC

|                                |                                |
|--------------------------------|--------------------------------|
| Model Name                     | W26L100-CHA2                   |
| Viewable Size Image            | 26"(16:9)                      |
| Active Display Area(mm)        | 575.769(H)x323.712(V)          |
| Pixel Pitch(mm)                | 0.4215x0.4215mm                |
| Number of Pixels               | 1366x768                       |
| Contrast Ratio                 | 2500:1(typ.)                   |
| Display Color                  | 16.7M(8bit/colors)             |
| Brightness(cd/m <sup>2</sup> ) | 450                            |
| Viewing Angle(CR>=10)          | -88~88(H); -88~88(V)           |
| Synchronization Range          |                                |
| Horizontal/Vertical            | 31.5~60.0KHz/60~75Hz           |
| Recommended Resolution         | 1366x768@ 60Hz                 |
| Signal Connector               | 15 pin D-sub                   |
| Power Source                   | AC100~240V, Universal, ±10%    |
| Power Consumption              | 145W typical, normal operation |
| Power Management               | VESA DPMS Compliant            |
| Plug & Play                    | VESA DDC 1/2B                  |
| Optional Video Input           | S-Video, Composite             |
| Optional DVI Input             | Yes                            |
| Touch Screen                   | SAW                            |

Remarks: W26L100 series= VGA Input only

W26L110 series= VGA+Video Input

### Mechanical Drawing

