

Rear Mount LCD

Wide Temperature Range LCD

15"

Specifications

RoHS
COMPLIANT
2002/95/EC

Model Name	R15L600-RMM2WT
Viewable Size Image	15"
Active Display Area(mm)	304.1(H)x228.1(V)
Pixel Pitch(mm)	0.297(H)x0.2973(V)
Number of Pixels(DOT)	1024x768
Contrast Ratio	350:1(typ.)
Display Color	16.7M(8bit/color)
Brightness(cd/m ²)	400
Viewing Angle(CR>=10)	-85~85(H); -80~70(V)
Synchronization Range	31.5~60.0KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	1024x768@60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, $\pm 10\%$
Power Consumption	30W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive, SAW, IR
System Operating temp	-20($^{\circ}$ C)(ambient temp)
	~55($^{\circ}$ C)(internal temp)

Remarks: R15L600 series= VGA input only

R15L630 series= VGA+Video Input



Mechanical Drawing

